



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification<sup>6</sup> :</b> <b>H04N 1/60</b>	<b>A2</b>	<b>(11) International Publication Number:</b> <b>WO 98/12867</b> <b>(43) International Publication Date:</b> 26 March 1998 (26.03.98)
<b>(21) International Application Number:</b> PCT/US97/16118 <b>(22) International Filing Date:</b> 19 September 1997 (19.09.97)  <b>(30) Priority Data:</b> 08/717,102      20 September 1996 (20.09.96)      US  <b>(71) Applicant:</b> ERICSSON INC. [US/US]; 7001 Development Drive, P.O. Box 13969, Research Triangle Park, NC 27709 (US).  <b>(72) Inventors:</b> HAYES, John, J.; 2408 Canonbie Lane, Wake Forest, NC 27587 (US). IRVIN, David, R.; 3101 Churchill Road, Raleigh, NC 27607 (US). ERICSSON, Ted, G.; Strandangsgatan 11, S-234 33 Lomma (SE). RASMUSSEN, Jim, A., J.; Sillarod Skola, S-277 57 Brosarp (SE).  <b>(74) Agent:</b> LASTOVA, John, R.; Nixon & Vanderhye, P.C., Suite 800, 1100 North Glebe Road, Arlington, VA 22201 (US).		<b>(81) Designated States:</b> AL, AM, AT*, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>Without international search report and to be republished upon receipt of that report.</i>
<b>(54) Title:</b> AN IMPROVED AUDIO-OUTPUT FOR HANDS-FREE PORTABLE TELEPHONE ACCESSORY  <b>(57) Abstract</b> <p>A wireless telephone communication device is operated in a hands-free mode with detected received audio being relayed for output on the speakers of a radio. A single two-frequency FM transmitter or a multi-frequency transmitter that transmits simultaneously on a plurality of channels relays the audio to the FM radio.</p>		

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

## **AN IMPROVED AUDIO-OUTPUT FOR HANDS-FREE PORTABLE TELEPHONE ACCESSORY**

### **FIELD OF THE INVENTION**

5

The invention is in the field of hands-free portable cellular telephone equipment. More particularly, the invention relates to the use of an FM radio as part of a hands-free system.

10

### **BACKGROUND OF THE INVENTION**

As the RF performance of a hand-held cellular telephone increases, the likelihood that it will be used by the driver of a moving vehicle also increases. This raises a safety concern. In response to this concern, the hands-free accessory to the cellular telephone has evolved. The basic purpose of the hands-free accessory is to affix the cellular telephone to the vehicle in an advantageous way, and thereby free the driver from distractions having to do with holding, manipulating and positioning the telephone.

20

Because the hands-free unit is an external accessory to the vehicle as well as to the telephone, the hands free-unit must live within certain design constraints. Among the most pressing of these constraints are physical bulk and aesthetics, both of which impose strict limits on the size of loudspeakers and the capacity of related audio components that can be included in the hands-free unit. As a result, hands-free units on the market today generally have poor audio-output characteristics, which compromise their effectiveness in the high-noise environment that is typical of a moving vehicle.

30

**SUBSTITUTE SHEET (RULE 26)**

The prior art offers several devices to combat the limitations outlined above, but none is entirely satisfactory.

One device from the prior art is an automatic mute device for the vehicle's AM/FM radio. Such a device senses the presence of RF energy emanating from the transmitter of a cellular telephone that is powering-up to engage in a call and mutes the radio.

In U.S. Patent No. 5,404,391, an automatic mute device comprising an antenna connected to a tuned circuit is used to sense voice channel activity on the cellular telephone. In response to sensing voice activity, the device provides a signal which disconnects power to the radio.

Another kind of automatic mute device, interposed in the audio path between the radio output and the vehicle's speakers, serves to interrupt the audio path and thereby mute the radio output in response to the electrical signal when that cellular telephone is actively engaged. This approach does nothing, of course, to improve the audio output quality of the cellular telephone, although it does remove an important source of interfering audio noise.

In a prior art refinement of the device just described, the automatic mute device includes its own power output audio amplifier. When the vehicle's radio is muted, the mute device also switches the vehicle's loudspeakers from the output of the radio to the output of the mute device's internal amplifier, and thereby makes the vehicle's speakers available to the audio signal produced by the cellular telephone.

This approach improves the audio output quality of the cellular telephone. Unfortunately, the installation of such a device is somewhat involved, as the vehicle's plurality of speakers must be routed through and controlled by the mute device. Also the volume of the mute device's audio output needs to be re-set as the level of external noise changes. Perhaps more importantly, the power output audio stages already present in the radio are unproductively duplicated in the mute device, thereby leading to unnecessary cost. Moreover, the DC electrical power required by the added power output audio stages is significant, which necessitates the presence and expense of a heavy-duty electrical service to the automatic mute device.

### OBJECTS OF THE INVENTION

It is an object of the invention to provide a hands-free communicator, such as a portable cellular telephone, operation with improved audio-output quality.

It is a further object of the invention to provide a hands-free portable communication device operation with increased audio output power.

Another object of the invention is to provide a hands-free portable cellular telephone with increased audio output power and good audio-output quality that is easy to install.

Another object of the invention is to provide a hands-free portable communication device operation with voice audio output over the speakers of a radio.

Another object of the invention is to provide a hands-free portable cellular telephone component of reduced physical size and DC power requirements.

5

### **BRIEF DESCRIPTION OF THE INVENTION**

A portable communication device such as a cellular telephone unit or an accessory is provided with an AM (amplitude modulated) or FM (frequency modulated) transmitter for transmitting in the commercial AM or FM radio frequency band. The AM or FM transmitter relays the audio information to the AM/FM radio receiver which outputs the audio in a conventional manner over the radio speakers. This provides for high quality audio output, particularly in the environment of an automobile.

15

In one embodiment of the invention, an AM or FM transmitter is constructed within or attached to the case of the portable cellular telephone unit. In other embodiments, the AM or FM transmitter is constructed in an accessory component which is adapted to hold or cradle the portable cellular telephone unit. A call activity detector is used to detect call activity and switch the vehicle AM/FM radio from commercial broadcast reception to reception from the AM or FM transmitter in the accessory.

25

The FM transmitter may be constructed as a simple two-frequency unit wherein it is tuned to broadcast on one of two adjacent FM channels. Alternatively, where constructed in an accessory, the FM transmitter may be constructed to broadcast simultaneously on a plurality of FM channels.

30

### **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 shows a first embodiment of the present invention, wherein a limited-range transmitter is integrated with the cellular telephone;

5

Fig. 1a illustrates a first form of a simple two-frequency FM transmitter;

Fig. 1b illustrates a second form of a simple two-frequency FM transmitter;

10

Fig. 2 shows an alternative of the first embodiment where an FM transmitter is in an accessory;

Fig. 3 shows a second embodiment of the invention where an FM transmitter is constructed in an accessory along with a call activity detector for switching a vehicle radio to receive the output of the FM transmitter;

15

Fig. 3a illustrates a second version of the second embodiment; and

20

Fig. 4 shows an FM transmitter for transmitting simultaneously on plural FM channels.

25

### **DESCRIPTION OF THE PREFERRED EMBODIMENTS**

The invention is described with reference to an FM transmitter in a portable cellular telephone. The invention is, however, not limited to such as the transmitter in the various embodiments may be an AM transmitter for use with an AM radio and the cellular telephone may be

30

SUBSTITUTE SHEET (RULE 26)

any wireless telecommunications device, e.g., a portable telephone, a police or public service hand-held communicator.

In a first embodiment, a low-power (few tens of milliwatts),  
5 limited range transmitter is constructed within the case that houses a cellular telephone unit. When engaged in a call, the transmitter relays incoming audio signals from the cellular telephone unit to the vehicle's radio via a wireless link. The radio receiver circuits detect and amplify the relayed signal and output the resulting audio to the vehicle's  
10 speakers, thereby providing high quality audio.

Figure 1 illustrates this embodiment in its simplest form. Within the casing 2 of portable cellular telephone unit 1 there is constructed conventional telephone receiving/transmitting and processing circuits 3  
15 (which may include a microprocessor), speaker 7, audio amplifier 8, battery 6, and in accordance with the invention a transmitter 10, switch 16 and frequency control element 15. Portable unit 1 in addition to conventional antenna 4 has an antenna 5 for transmitting an RF signal in the commercial radio band for reception by a radio.

20

The transmitter 10 constructed as an FM transmitter has the capability to operate on two frequencies that fall on adjacent channels within the commercial FM radio broadcast band (88-108 MHz). Since commercial broadcast is not allowed on adjacent channels, at least one  
25 of the two frequencies will be clear. The low-power, FM transmitter output frequency is set to a clear channel. This setting is during initial installation of the system in the vehicle by manipulation of frequency control element 15 which may be a tuning control or a switch.

30 A switch 16 provided on the portable telephone casing 2 is associated with the activation of the FM transmitter 10. Upon switching



to the hands-free mode, switch 16 as illustrated connects DC power from battery 6 to FM transmitter 10, disconnects power to audio amplifier 8 and switches the input audio signal to output amplifier 8 to an FM modulator in the FM transmitter 10. In the hands-free mode, it is  
5 advantageous to disconnect or remove audio from the telephone speaker 7 to discourage or prevent its use in the conventional mode, i.e., with the speaker adjacent the user's ear, since the FM transmitter is transmitting RF energy. This also allows for the use in the hands-free mode of a cellular transmitter with greater output power. Moreover, by  
10 not driving the telephone speaker 7 during the hands-free use, the battery power of the telephone battery 6 is conserved.

Further illustrated in Figure 1 is a conventional FM radio 20 with its antenna 21 coupled to FM receiver 22. The FM receiver 22 is  
15 connected to one or more speakers 23.

A user of the unit desiring a hands-free operation, manipulates switch 16 on casing 2 of the cellular telephone unit 1 to the hands-free position and tunes or sets FM radio 20 to the frequency of the low-  
20 power FM transmitter 10. The cellular telephone unit 1 is clipped onto the sun visor of the vehicle or secured in any convenient manner that facilitates a hands-free use.

Figure 1a illustrates a simple and an economical FM transmitter  
25 10 that may be constructed in the casing 2. It comprises a conventional FM modulator 11, and an oscillator 12 that is tunable over a range (~200 kHz) that encompasses at least two FM broadcast channels. A tunable output tank circuit 13 in the oscillator is tuned by frequency control element 15 through tuning of a coil. In the initial installation as describe  
30 above, the frequency control element 15 is used to tune the oscillator 12.

carrier frequency to an FM frequency corresponding to that of a clear FM radio channel.

Figure 1b illustrates another version of an FM transmitter that may be incorporated in the casing 2. Here there are two FM carrier oscillators 12a and 12b, and element 15 is merely a switch for connecting one of the oscillators to the FM modulator 11 for causing the FM transmitter 10 to transmit at one of two adjacent FM channel commercial broadcast frequencies. This provides for an easier initial setting as the switch merely is moved between two positions while listening to the FM radio tuned to the clear channel. While one switching arrangement is shown, other arrangements for connecting one oscillator or the other to the FM modulator would be apparent to one skilled in this art.

Figures 1a and 1b are only illustrative of the manner in which the FM transmitter 10 can be constructed to transmit at either one of two FM broadcast channel frequencies. A phase locked loop with a processor which changes the division factor would be another arrangement. Modifications of the circuit of Figure 3, described herein, to transmit the two frequencies would be another means for providing the two requisite FM frequencies.

In an alternative version of the Figure 1 embodiment, the FM transmitter 10 is incorporated within a case 31 that houses a hands-free accessory unit 30 as shown in Figure 2. The hands-free accessory unit in this version is a device which holds or cradles the portable cellular telephone unit. A power ON/OFF switch 33 is manipulated to the ON position for hands-free use. The power line to the FM transmitter 10 may alternatively or additionally be interlocked at 35a via an audio signal detection circuit 35 such that the FM transmitter is off in the

SUBSTITUTE SHEET (RULE 26)

absence of detected audio signals. Power for operating the FM transmitter is provided from a battery 37 in the accessory or alternatively from the vehicle's electrical system. Detected audio signals are connected from the cellular telephone unit 1 to the  
5 accessory 30 via connection pins 19 of an electrical connector joining the telephone to the accessory when set in the accessory. In this alternative, the FM clear channel is selected manually by control 15 at the time the hands free-unit is installed. FM broadcast band signals are transmitted via antenna 5 to the FM radio 20 in the vehicle.

10

In either alternative of the first embodiment, ease of installation is a paramount feature since no modification of the vehicle radio is required. There is no electrical connection between the vehicle radio and the cellular telephone or the accessory.

15

In a second embodiment of the present invention, as shown in Figure 3, FM transmitter 10 is housed in accessory 30 and the output of the FM transmitter is connected by a shielded cable 39 to the RF input of the vehicle radio. Because of the direct connection between the FM  
20 transmitter 10 and the radio 20 and further because of the shielding of this connection, the possibility of RF transmission outside the vehicle is greatly reduced.

As shown in Figure 3, wherein like components are numbered the same as in Figure 1, FM transmitter 10 is located in hands-free  
25 accessory 30. The hands-free accessory 30 receives audio signals from the portable telephone unit via a direct connection when the portable cellular telephone unit 1 is held by or is otherwise mounted in physical contact therewith. Standard connection pins 19, provide electrical  
30 connections between the cellular telephone unit 1 and accessory 30.

SUBSTITUTE SHEET (RULE 26)

Hands-free accessory 30 is connected by shielded cable 39 to the FM radio 20.

Also constructed within the hands-free accessory 30 is a call  
5 activity detector 32, which upon the detection of telephone activity  
actuates a switch 38 to switch the RF input from the antenna 21 to the  
FM transmitter 10 output. Actuation of switch 38 establishes a direct  
electrical connection between the cellular telephone and the RF input of  
the radio. Call activity detector 32 may be an automatic mute device,  
10 similar as in prior art mute devices, in that it by an RF pick-up device  
physically located within the casing of the accessory and illustrated  
schematically at 34, senses the cellular telephone activity by picking up  
signals on a voice channel frequency in the cellular telephone band (824  
to 844 MHz). As such, the call activity detector 32 is basically a voice  
15 activity detector comprised of a tuned circuit 70 tuned to pickup RF  
signals in the cellular telephone band, an amplifier 71 in which the  
signals are amplified and a detector 72 that detects either the RF signal  
or a modulating signals on the RF and provides an actuating signal. The  
actuating signal of device 32, however, unlike prior art mute devices, is  
20 not used to silence the radio speakers or cut off power to the radio, but  
connects the radio to the FM transmitter 10 RF output by actuation of  
switch 38. Thereby, the radio speakers support the radio in its new role  
as an extended audio system of the cellular telephone. The voice  
activity detector may sense RF radiation in the cellular telephone band  
25 by means of an electromagnetic radiation pickup device, e.g., an  
antenna, or alternatively it may be directly connected (as shown in  
dotted lines) to the circuitry in the cellular telephone unit via connection  
pins to detect call activity, e.g., a call in progress, origination of an  
outgoing call, or paging to accept and incoming call.

As in the first embodiment, the user of the system tunes or sets the radio 20 to a predetermined frequency on which the FM transmitter 10 is operating when the phone is engaged. The predetermined frequency is selected, the same as above, when the  
5 hands-free accessory is installed.

In this embodiment, because of the shielded cable 39 connection, the possibility of RF transmissions from the FM transmitter 10 to outside the vehicle is reduced, the FM transmitter 10 is not located in the  
10 hand-held portable cellular telephone unit 1, and power for the FM transmitter 10 does not come from the battery of the cellular telephone unit but from a battery in the accessory or from the vehicle's electrical system.

15 A variation of the second embodiment is shown in Figure 3a. A decoder 42 is used as the call activity detector. Electronic equipment in the cellular telephone unit 1 operating under microprocessor 18 control includes a system bus 18a on which commands and data are exchanged among the processor and the devices that it controls. Commands are  
20 provided to indicate a plurality of states, including "call in progress", "outgoing call origination" and "incoming call page." These states are represented by unique bit patterns on the system bus 18a. The decoder 42 of Figure 3a, which may comprise discrete digital logic circuits or a second microprocessor, monitors the cellular telephone  
25 system bus 18a, decodes commands that appear on that bus, compares the decoded values to predetermined values that denote the three states, "call in progress", "outgoing call origination" and "incoming call page" and generates an electrical signal whenever one of the three states is detected. Thus, the decoder 42 decodes commands on the system  
30 bus 18a of the cellular telephone, determines therefrom the presence of telephone activity and generates an electrical signal that actuates

switch 38 to connect the output of FM transmitter 10 to the RF input of the radio 20.

In the second embodiment, the switch 38 is shown to be located  
5 at the radio, but it may also be located at the accessory 30, with the shielded cable 39 connected between the output terminal of switch 38 and the RF input of radio 20.

The switch actuating signal from device 32 or 42 may be applied  
10 to a further switch 17 to connect power to the FM transmitter 10. The power may be provided to the accessory 30 by connection to the vehicle's electrical system, or a battery may be provided within the housing of the accessory.

Further, the switch actuating signal from device 32 or 42 may  
15 also be used to actuate a switch 24 to turn on the radio 20. This way, in the event the radio is off, the vehicle operator is not required to assess the fact that the system is not operating in the hands-free mode and determine that it is because the radio is off. Switch 24 is in shunt with  
20 the ON/OFF radio switch and is switched to the ON state by the device 30 detecting call activity. A switch 25 may also be actuated by the electrical signal to switch the radio 20 to the FM mode, if in an AM, cassette playing, or CD disc playing mode. These connections are easily made on a radio with remote control facilities.

25

Figure 4 illustrates an FM transmitter that may advantageously be  
used in the second embodiment in lieu of the hereinbefore described two-frequency FM transmitter. This is a more complex transmitter that transmits simultaneously on a plurality of channels within the FM  
30 broadcast band. With this transmitter, it is no longer necessary for an occupant of the vehicle to tune or set the frequency of the radio in

SUBSTITUTE SHEET (RULE 26)

response to a telephone call, because the call will be rebroadcast to the radio over all the FM channels. This is an improvement having the important safety advantage of further minimizing the diversion of a driver's attention.

5

In Figure 4, block 51 comprises a frequency synthesizer of PLL (phase lock loop) design which includes VCO (voltage controlled oscillator) 65, a divide-by-N unit 64, phase detector 63, and filter 62. A summing circuit 61 is inserted between filter 62 and VCO 65 to  
10 facilitate the introduction of audio signals from the cellular telephone unit. A frequency reference is provided to the phase detector 63 by a divide-by-two circuit 57 which provides a 100 kHz signal to the phase detector by dividing the output of 200 kHz reference oscillator 52.

15 In an exemplary operation, the VCO 65 oscillates at 98.1 MHz, and N in the divide-by-N unit 64 is set to 981 to provide a 100 kHz signal to one input of phase detector 63 for comparison with the 100 kHz reference signal from unit 57 at the other input. The phase difference between the two 100 kHz signals is provided to VCO 65 via  
20 summing circuit 61 to lock the VCO to the phase of oscillator 52. Audio from the cellular telephone unit introduced at summing circuit 61 modulates the VCO output frequency.

Turning to the overall circuit of Figure 4, in addition to the  
25 modulated synthesizer 51, divide-by-two circuit 57 and reference oscillator 52, the FM transmitter comprises harmonic generator/amplifier 53 connected to the output of reference oscillator 52, bandpass filter 54 connected to receive the output from harmonic generator/amplifier 53 and a mixer 55 for mixing the outputs from  
30 bandpass filter 54 and the VCO modulated synthesizer 51. A second bandpass filter 56 filters the output from the mixer 55.

SUBSTITUTE SHEET (RULE 26)

Continuing with the exemplary operation, modulated synthesizer 51 operates at 98.1 MHz and reference oscillator 52 operates at 200 kHz. The output of reference oscillator 52 is input to harmonic generator/amplifier 53 which produces output signals at integer multiples of 200 kHz. These harmonics are filtered by bandpass filter 54, which attenuates harmonics falling outside the useful range of frequencies, above the 49th harmonic. Mixer 55 combines the modulated 98.1 MHz signal from synthesizer 51 with the various harmonics, and outputs simultaneous modulated signals having frequencies that fall on the various commercial FM broadcast channels above and below 98.1 MHz. For example, combining the third harmonic (600 kHz) with the modulated signal at 98.1 MHz results in modulated output signals at 98.7 and 97.5 MHz. Likewise, the fourth harmonic combined with the modulated signal at 98.1 MHz produces outputs at 98.9 and 97.3 MHz. The output of mixer 55 is filtered by a bandpass filter 65 having a passband of 88-108 MHz. The output of the filter is connected to switch 38.

Although one particular structure for the multi-frequency transmitter is set forth in Figure 4, other variations of the multi-frequency transmitter structure will be apparent to those of ordinary skill in the art of RF design. Therefore, the structure shown in Figure 4 is by way of example only rather than by way of limitation.

25

The operation frequencies described are those nominally employed in the U.S. The invention is not limited to the described frequencies. A microphone may be associated in a conventional manner with the accessory to further facilitate the hands-free operation.

30 Switches, such as 17, 24, 25 and 38 may take the form of a transistor, an

**SUBSTITUTE SHEET (RULE 26)**



integrated circuit, or other solid state devices as will be appreciated by those skilled in the art.

While the invention has been described in connection with what  
5 is presently considered to be the most practical and preferred  
embodiment, it is to be understood that the invention is not to be limited  
to the disclosed embodiment, but on the contrary, is intended to cover  
various modifications and equivalent arrangements included within the  
spirit and scope of the appended claims.

**WHAT IS CLAIMED IS:**

1. A wireless communication unit having an antenna for receiving communication signals of a communication system and a  
5 receiver for processing the received communication signals to provide audio signals for driving a speaker in the unit comprising:  
a transmitter for transmitting RF signals in the commercial broadcast band for radios, said transmitter being coupled to receive said audio signals as modulating input signals.  
10
2. A wireless communication unit as in claim 1 wherein the transmitter is an FM transmitter including means for selectively setting said FM transmitter to transmit the RF signals at the frequency of one of two adjacent channels in the FM commercial broadcast band.  
15
3. A wireless communication unit as in claim 1, including means for switching power to the speaker of the unit OFF, power to the transmitter ON and increased power to a transmitter for transmitting a higher power signal in a unit hands-free mode of use, said means  
20 ensuring that power to the transmitter is OFF and increased power to transmitter for transmitting a higher power signal is inhibited in a normal unit hand-held mode of use.
4. A wireless communication unit as in claim 1, further  
25 comprising an additional antenna coupled to the transmitter for wireless transmission of the RF signals to a radio.
5. A wireless communication unit as in claim 4 wherein said transmitter is located within a casing of the unit and said additional  
30 antenna is carried by said casing.

6. A method of producing the audio output from voice modulated received signals over a voice communication channel of a portable communication unit comprising,  
converting the voice modulated received signals received in a  
5 first frequency band to voice modulated RF signals in the commercial frequency band for a radio, and  
transmitting said voice modulated RF signals at low power to a radio for production of the audio output.
- 10 7. A method as in claim 6 wherein said transmitting is via a wireless link.
8. A method as in claim 7 wherein said transmitting is over a clear channel in the frequency band of an FM radio.
- 15 9. A method as in claim 6 wherein said transmitting is via a shielded cable.
10. A method as in claim 9 wherein said transmitting is at  
20 simultaneous multiple frequencies in the commercial frequency band of an FM radio.
11. An accessory for a portable communication unit comprising, a transmitter for transmitting RF signals in the commercial  
25 broadcast band for radios, said transmitter being adapted to receive as a modulating input signal audio signals produced in a voice receiving section of the portable communication unit.
12. An accessory as in claim 11 further comprising, an antenna coupled to the transmitter for wireless transmission of  
30 said RF signals to a radio.
13. An accessory as in claims 11 further comprising,

a call activity detector for detecting call activity at the portable communication unit and actuating a first switch to connect the RF output of the transmitter to the RF input of a radio.

5           14. An accessory as in claim 13 further comprising,  
a shielded cable connecting the RF output of the transmitter to an input terminal of said first switch.

10           15. An accessory as in claim 13 further comprising,  
a shielded cable connecting an output of said first switch to the RF input of said radio.

15           16. An accessory as in claim 11 further comprising control means for selectively operating said transmitter at one of two frequencies of adjacent channels in the commercial FM broadcast band.

20           17. An accessory as in claim 11 wherein said transmitter transmits simultaneously on a plurality of channels in the FM broadcast band.

25           18. An accessory as in claim 17 wherein said transmitter comprises,  
a phase lock loop modulated synthesizer for receiving said audio signals and outputting an audio modulated FM signal,  
a harmonic generator for providing harmonics of a reference signal, and  
a mixer for mixing the audio modulated FM signal and the harmonics to produce simultaneously a plurality of FM signals.

19. An accessory as in claim 13 wherein said call activity detector comprises a decoder for detecting and decoding commands on a system bus of a portable cellular telephone.


5           20. An accessory as in claim 13 and said call activity detector further actuating a second switch to turn on the radio, and a third switch to cause the radio to be in the FM mode.

          21. An accessory as in claim 20 and said call activity detector  
10 further actuating a fourth switch to provide power to the FM transmitter.

          22. An FM transmitter for transmitting RF signals comprising,  
a modulator for modulating audio signals and outputting a  
modulated FM signal,  
15 a harmonic generator for providing harmonics of a reference  
signal, and  
a mixer for mixing the modulated FM signal and the harmonics  
to produce a simultaneous transmission of a plurality of FM signals.

          23. An FM transmitter as in claim 22 wherein said phase lock  
20 loop modulated synthesizer includes a summing circuit for receiving  
said modulating audio signals for modulating an FM carrier frequency  
produced in the phase lock loop.

          24. An FM transmitter as in claim 23 wherein said phase lock  
25 loop modulated synthesizer is phase locked to said reference signal.



SUBSTITUTE SHEET (RULE 26)

FIG. 1A





FIG. 1B







FIG. 2





**FIG. 3**

5/6





FIG. 3A

SUBSTITUTE SHEET (RULE 26)

6/6



SUBSTITUTE SHEET (RULE 26)

FIG. 4


**THIS PAGE BLANK (USPTO)**



## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<b>(51) International Patent Classification <sup>6</sup>:</b>  <b>H04B 1/38, H04M 1/60</b>	<b>A3</b>	<b>(11) International Publication Number:</b> <b>WO 98/12867</b>  <b>(43) International Publication Date:</b> 26 March 1998 (26.03.98)
<b>(21) International Application Number:</b> PCT/US97/16118  <b>(22) International Filing Date:</b> 19 September 1997 (19.09.97)  <b>(30) Priority Data:</b> 08/717,102      20 September 1996 (20.09.96)      US  <b>(71) Applicant:</b> ERICSSON INC. [US/US]; 7001 Development Drive, P.O. Box 13969, Research Triangle Park, NC 27709 (US).  <b>(72) Inventors:</b> HAYES, John, J.; 2408 Canonbie Lane, Wake Forest, NC 27587 (US). IRVIN, David, R.; 3101 Churchill Road, Raleigh, NC 27607 (US). ERICSSON, Ted, G.; Strandangsgatan 11, S-234 33 Lomma (SE). RASMUSSEN, Jim, A., J.; Sillarod Skola, S-277 57 Brosarp (SE).  <b>(74) Agent:</b> LASTOVA, John, R.; Nixon & Vanderhye, P.C., Suite 800, 1100 North Glebe Road, Arlington, VA 22201 (US).		<b>(81) Designated States:</b> AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).  <b>Published</b> <i>With international search report.</i>  <b>(88) Date of publication of the international search report:</b> 8 October 1998 (08.10.98)

**(54) Title:** AN IMPROVED AUDIO-OUTPUT FOR HANDS-FREE PORTABLE TELEPHONE ACCESSORY

**(57) Abstract**

A wireless telephone communication device is operated in a hands-free mode with detected received audio being relayed for output on the speakers of a radio. A single two-frequency FM transmitter or a multi-frequency transmitter that transmits simultaneously on a plurality of channels relays the audio to the FM radio.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

# INTERNATIONAL SEARCH REPORT

Intern. Appl. No.

PCT/US 97/16118

**A. CLASSIFICATION OF SUBJECT MATTER**  
IPC 6 H04B1/38 H04M1/60

According to International Patent Classification (IPC) or to both national classification and IPC

**B. FIELDS SEARCHED**

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 H04M H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

**C. DOCUMENTS CONSIDERED TO BE RELEVANT**

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X Y A	<p>GB 2 264 613 A (PIONEER ELECTRONIC CORP) 1 September 1993 see abstract see page 3, line 11 - line 19</p> <p>see page 6, line 14 - line 23 see page 14, line 18 - page 15, line 13 see page 16, line 18 - page 22, line 1 see page 23, line 13 - line 16 see figure 1 see figure 5 see figure 6 see figure 7</p> <p style="text-align: center;">--- -/-</p>	<p>1,3-8, 11,12 9,17 2,10,13, 16,18</p>

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

\* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

5 June 1998

Date of mailing of the international search report

26.06.98

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Lindhardt, U

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 97/16118

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 463 356 A (PALMER JAMES K) 31 October 1995	22
Y	see abstract see column 1, line 1 - column 2, line 11 see figure 1 see figure 5	17
A	-----	10,18,23
Y	US 2 959 644 A (MOTOROLA INC.) 8 November 1960	9
A	see abstract see column 1, line 1 - line 72 see column 4, line 26 - column 5, line 18 see figure 3 see figure 4 -----	10,14,15



# INTERNATIONAL SEARCH REPORT

International application No.

PCT/US 97/ 16118

## Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:  
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:  
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:  
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

## Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

see additional sheet

1. ☒ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☒ No protest accompanied the payment of additional search fees.

## INTERNATIONAL SEARCH REPORT

International Application No. PCT/US 97/16118

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. Claims: 1 - 8, 11 -12, 16

FM transmitter that can be tuned between two adjacent channels

2. Claims: Claims 6, 9 - 11, 13 - 15, 19 - 21

Switching of the antenna input of the FM receiver between an antenna and a FM transmitter.

3. Claims: Claim 11, 17 - 18, 22 - 24

FM transmitter that transmits simultaneously on multiple or all FM broadcast channels.

# INTERNATIONAL SEARCH REPORT

Information on patent family members

Intern. Application No

PCT/US 97/16118

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
GB 2264613 A	01-09-1993	NONE	
US 5463356 A	31-10-1995	NONE	
US 2959644 A	08-11-1960	NONE	

**THIS PAGE BLANK (USPTO)**